




PRODUCT MATERIAL	Die-cast aluminium
LIGHT SOURCE	Bridgelux V8
MODULE LIFETIME	Approx. 35.000 hours
LED COOLING	Passive cooling
COLORS	See ring options
BEAM ANGLE	 33°
ADJUSTABLE	No
SIZE	83 X 74MM


OPTIONS

DIMMABLE DRIVERS 350mA <small>IN COMBINATION WITH THIS LUMINAIRE. ADDITIONAL PRICE.</small>	1/10v Dimmable 350mA 10W art. no.: 0110.350.10.1	€ 29,50
	Phase-cut Dimmable 350mA 10W art. no.: 0110.350.10.1	€ 29,50
	Dimmable DALI 350mA 18W art. no.: 0118.350.75.0	€ 55,00
DIMMABLE DRIVERS 500mA <small>IN COMBINATION WITH THIS LUMINAIRE. ADDITIONAL PRICE.</small>	1/10v Dimmable 500mA 10W art. no.: 0110.500.10.1	€ 29,50
	Phase-cut Dimmable 500mA 10W art. no.: 0110.500.10.1	€ 29,50
	Dimmable DALI 500mA 18W art. no.: 0118.500.75.0	€ 55,00




INFORMATION

Incl. driver, cable and plug.

Keylight International reserves the right to modify or change technical, construction or LED specifications due to continuous improvements of our products and lightsources.



ALPHA WHITE



ART.NR.	COLOR	LAMP TYPE	BRAND	LUMINOUS FLUX	OUTPUT POWER	MODULE EFFICIENCY	COLOUR TEMPERATURE	CRI	TC LIFETIME	mA
5107.994.35.3	○ White	V8	Bridgelux	550LM	6,2W	88LM/W	2700K	>90	35.000 Hrs	350
5107.994.35.35	○● White / black	V8	Bridgelux	550LM	6,2W	88LM/W	2700K	>90	35.000 Hrs	350
5107.994.35.5	● Black	V8	Bridgelux	550LM	6,2W	88LM/W	2700K	>90	35.000 Hrs	350
5107.994.35.59	●● Black / gold	V8	Bridgelux	550LM	6,2W	88LM/W	2700K	>90	35.000 Hrs	350
5109.994.50.3	○ White	V8	Bridgelux	745LM	9,2W	80LM/W	2700K	>90	35.000 Hrs	500
5109.994.50.35	○● White / black	V8	Bridgelux	745LM	9,2W	80LM/W	2700K	>90	35.000 Hrs	500
5109.994.50.5	● Black	V8	Bridgelux	745LM	9,2W	80LM/W	2700K	>90	35.000 Hrs	500
5109.994.50.59	●● Black / gold	V8	Bridgelux	745LM	9,2W	80LM/W	2700K	>90	35.000 Hrs	500