## **KEY**LIGHT



PRODUCT MATERIAL	Steel and aluminium			
LIGHT SOURCE	Philips LEDLine			
MODULE LIFETIME	Approx. 50.000 hours			
LED COOLING	Passive cooling			
DRIVER	Incl. standard Philips driver.			
COLORS (A)	○ <b>3</b> = RAL 9003 white			
	<b>5</b> = RAL 9005 black			
	<b>6</b> = RAL 9006 alu			
REFLECTOR PLATE	Opal diffuser			
SURFACE MOUNTED	Direct / Indirect luminaire			



## OPTIONS

SIZE

COLORS	Available in all RAL colours on request			
	Additional price + 10%			
DIMMABLE	Dimmable DALI	€ 60,00		
EMERGENCY BALLAST	0187.003.01 1 hour	€ 180,00		
PENDENT	Also available as a pendent version on req.			

500 X 99MM

## INFORMATION


WARRANTY

∆ see colors

5 Years

Keylight International reserves the right to modify or change technical, contruction or LED specifications due to continuous improvements of our products and lightsources. The light source in this product can be replaced with an equivalent module made by Philips, Osram or Tridonic.





ART.NR.	LAMP TYPE	BRAND	LUMINOUS FLUX	OUTPUT POWER	MODULE EFFICIENCY	COLOUR TEMPERATURE	CRI	TC LIFETIME	POWER FACTOR
∆ see color									
5430.195.91∆	LEDLine	Philips	5000LM	45W	111LM/W	3000K	>80	50.000	>0,9
5430.196.91∆	LEDLine	Philips	5000LM	45W	111LM/W	4000K	>80	50.000	>0,9