


ARTICLE NO.	DESCRIPTION	PROFILE	COVER	INNER WIDTH	SIZE
PROFILE 35					
0635.000.00.6	Profile 35mm	Aluminium anodized	Incl. Opal		3000 X 35 X 35
Accessories					
0735.901.99.6	Endcap with cablehole				
0735.902.99.6	Encap w/o cablehole				




ARTICLE NO.	DESCRIPTION	PROFILE	COVER	INNER WIDTH	SIZE
PROFILE 68					
0668.000.00.6	Profile 68mm	Aluminium anodized	Incl. Opal		3000 X 68 X 35
Accessories					
0768.901.99.6	Endcap with cablehole				
0768.902.99.6	Encap w/o cablehole				
0768.200.00.6	Suspension kit 2x 200mm				



ARTICLE NO.	DESCRIPTION	PROFILE	COVER	INNER WIDTH	SIZE
STAIR					
0666.999.91.6	LEDLINE STAIR 45°	Aluminium anodized	Clear	12,2	2000 X 66,9 X 27,3
0666.999.90.6	LEDLINE STAIR 45°	Aluminium anodized	100% frosted	12,2	2000 X 66,9 X 27,3
0766.999.99.6	End cap	Aluminium grey			



ARTICLE NO.	DESCRIPTION	PROFILE	COVER	INNER WIDTH	SIZE
WALL					
0667.999.91.6	LEDLINE WALL	Aluminium anodized	Clear	12,2	2000 X 26,2 X 70
0667.999.90.6	LEDLINE WALL	Aluminium anodized	100% frosted	12,2	2000 X 26,2 X 70
0767.999.99.6	End cap	Aluminium grey			



ARTICLE NO.	DESCRIPTION	PROFILE	COVER	INNER WIDTH	SIZE
FLAT					
0673.999.91.6	LEDLINE FLAT	Aluminium anodized	Clear	12,2	2000 X 52,3 X 7,63
0673.999.90.6	LEDLINE FLAT	Aluminium anodized	100% frosted	12,2	2000 X 52,3 X 7,63
0734.999.99.6	End cap	With cable hole			
0733.999.99.6	End cap	Without cable hole			

The profile with choice of frosted diffuser is "LEDs DOTS FREE" and deliver soft smooth light on the whole surface.

The profile can accommodate standard led stripes up to 12mm of the wideness. It is quality and contemporary design which fits in many places.

Ledline is made from anodized aluminum with choice of high quality frosted ("LEDs DOTS FREE"), 50% frosted or transparent snap-in diffuser and matching end caps.

The snap-in diffuser is made from UV resistant material and it is damage resistant (walk over safe).

The aluminum profile is performing as the heat sink to the LEDs and also presents itself as nice, stylish housing where all components are matching and are high quality

Technical drawings whit measurements and mounting instructions are available on request.