



PRODUCT MATERIAL

Die-cast aluminium + aluminium

LIGHT SOURCE

SLM G6

MODULE LIFETIME

Approx. 50.000 hours

LED COOLING

Passive cooling

DRIVER

Incl. Xitanium driver.

COLORS (Δ)

○ 3 = RAL 9003 white

BEAM ANGLE

60°

ADJUSTABLE

Yes

SIZE

174 X 92MM



OPTIONS

EMERGENCY BALLAST

0187.003.01 1 hours. € 180,00

DIMMABLE

Dimmable DALI € 60,00

INFORMATION



TRITON

WARRANTY

5 Years

Δ = product color code. See colors

Keylight International reserves the right to modify or change technical, construction or LED specifications due to continuous improvements of our products and lightsources. The light source in this product can be replaced with an equivalent module made by Philips, Osram or Tridonic.



AVAILABLE SLM OPTIONS							
To order the correct product, please replace COB* in the article number field with the COB code found on the last page of the catalogue							
ARTICLE NUMBER Δ See colors	LUMINOUS FLUX	BRAND	OUTPUT POWER	COLOUR TEMPERATURE	CRI	SETTING	POWER FACTOR
4079. COB* .60.Δ	1100	Philips SLM G6	7W	827 / 830 / 835 / 840 / 850	>80	High Efficiency	>0,9
4079. COB* .60.Δ	1100	Philips SLM G6	8W	927 / 930	>90	High Efficiency	>0,9
4079. COB* .60.Δ	1100	Philips SLM G6	7W	830 Premium White	>80	High Efficiency	>0,9
4079. COB* .60.Δ	1100	Philips SLM G6	8W	930 / 935 / 940 Premium White	>90	High Efficiency	>0,9
4079. COB* .60.Δ	1100	Philips SLM G6	10W	930 Crisp White (930 CW)	>90	High Efficiency	>0,9
4079. COB* .60.Δ	1100	Philips SLM G6	11W	Food Warm White (FWW)	84	High Efficiency	>0,9
4079. COB* .60.Δ	1100	Philips SLM G6	11W	Food Premium Red (FPR)	88	High Efficiency	>0,9
4079. COB* .60.Δ	2000	Philips SLM G6	13W	827 / 830 / 835 / 840 / 850	>80	High Efficiency	>0,9
4079. COB* .60.Δ	2000	Philips SLM G6	17W	927 / 930	>90	High Efficiency	>0,9
4079. COB* .60.Δ	2000	Philips SLM G6	14W	830 Premium White	>80	High Efficiency	>0,9
4079. COB* .60.Δ	2000	Philips SLM G6	16W	930 / 935 / 940 Premium White	>90	High Efficiency	>0,9
4079. COB* .60.Δ	2000	Philips SLM G6	21W	930 Crisp White (930 CW)	>90	High Efficiency	>0,9
4079. COB* .60.Δ	2000	Philips SLM G6	21W	Food Warm White (FWW)	84	High Efficiency	>0,9
4079. COB* .60.Δ	2000	Philips SLM G6	20W	Food Premium Red (FPR)	88	High Efficiency	>0,9
4079. COB* .60.Δ	3000	Philips SLM G6	19W	827 / 830 / 835 / 840 / 850 / 857	>80	High Efficiency	>0,9
4079. COB* .24.Δ	3000	Philips SLM G6	26W	927 / 930	>90	High Efficiency	>0,9
4079. COB* .24.Δ	3000	Philips SLM G6	20W	830 Premium White	>80	High Efficiency	>0,9
4079. COB* .24.Δ	3000	Philips SLM G6	25W	930 / 935 / 940 Premium White	>90	High Efficiency	>0,9
! High efficiency is the standard Keylight setting for all SLM G6 LED modules. For technical and warranty information regarding high efficiency, see last page of the catalogue. Standard system warranty is 5 years.							