

VISION 15



<b>PRODUCT MATERIAL</b>	Die-cast aluminium
<b>LIGHT SOURCE</b>	SLM G6
<b>MODULE LIFETIME</b>	Approx. 50.000 hours
<b>LED COOLING</b>	Passive cooling
<b>DRIVER</b>	Incl. Xitanium driver.
<b>COLORS (Δ)</b>	<ul style="list-style-type: none"> <li>○ 3 = RAL 9003 white</li> <li>● 5 = RAL 9005 black</li> <li>● 6 = RAL 9006 alu</li> </ul>
<b>BEAM ANGLE</b>	
<b>ADJUSTABLE</b>	Yes
<b>SIZE</b>	146 X 137MM



OPTIONS

<b>EMERGENCY BALLAST</b>	0187.003.01 - 1 hours.	€ 180,00
<b>DIFFUSER</b>	0186.999.99 (frosted diffuser)	€ 9,50
<b>DIFFUSER W/ HOLE</b>	0188.999.99 (frosted diffuser)	€ 9,50
<b>DIMMABLE</b>	Dimmable DALI	€ 60,00



INFORMATION

<b>WARRANTY</b>	5 Years
-----------------	---------

Δ = product color code. See colors

Keylight International reserves the right to modify or change technical, construction or LED specifications due to continuous improvements of our products and light sources. The light source in this product can be replaced with an equivalent module made by Philips, Osram or Tridonic.

VISION 15



AVAILABLE SLM OPTIONS

To order the correct product, please replace **COB\*** in the article number field with the COB code found on the last page of the catalogue

ARTICLE NUMBER	LUMINOUS FLUX	BRAND	OUTPUT POWER	COLOUR TEMPERATURE	CRI	SETTING	POWER FACTOR
4021. <b>COB*</b> .24.Δ	1100	Philips SLM G6	7W	827 / 830 / 835 / 840 / 850	>80	High Efficiency	>0,9
4021. <b>COB*</b> .24.Δ	1100	Philips SLM G6	8W	927 / 930	>90	High Efficiency	>0,9
4021. <b>COB*</b> .24.Δ	1100	Philips SLM G6	7W	830 Premium White	>80	High Efficiency	>0,9
4021. <b>COB*</b> .24.Δ	1100	Philips SLM G6	8W	930 / 935 / 940 Premium White	>90	High Efficiency	>0,9
4021. <b>COB*</b> .24.Δ	1100	Philips SLM G6	10W	930 Crisp White (930 CW)	>90	High Efficiency	>0,9
4021. <b>COB*</b> .24.Δ	1100	Philips SLM G6	11W	<b>Food Warm White (FWW)</b>	<b>84</b>	High Efficiency	>0,9
4021. <b>COB*</b> .24.Δ	1100	Philips SLM G6	11W	<b>Food Premium Red (FPR)</b>	<b>88</b>	High Efficiency	>0,9
4021. <b>COB*</b> .24.Δ	2000	Philips SLM G6	13W	827 / 830 / 835 / 840 / 850	>80	High Efficiency	>0,9
4021. <b>COB*</b> .24.Δ	2000	Philips SLM G6	17W	927 / 930	>90	High Efficiency	>0,9
4021. <b>COB*</b> .24.Δ	2000	Philips SLM G6	14W	830 Premium White	>80	High Efficiency	>0,9
4021. <b>COB*</b> .24.Δ	2000	Philips SLM G6	16W	930 / 935 / 940 Premium White	>90	High Efficiency	>0,9
4021. <b>COB*</b> .24.Δ	2000	Philips SLM G6	21W	930 Crisp White (930 CW)	>90	High Efficiency	>0,9
4021. <b>COB*</b> .24.Δ	2000	Philips SLM G6	21W	<b>Food Warm White (FWW)</b>	<b>84</b>	High Efficiency	>0,9
4021. <b>COB*</b> .24.Δ	2000	Philips SLM G6	20W	<b>Food Premium Red (FPR)</b>	<b>88</b>	High Efficiency	>0,9
4021. <b>COB*</b> .24.Δ	3000	Philips SLM G6	19W	827 / 830 / 835 / 840 / 850 / 857	>80	High Efficiency	>0,9
4021. <b>COB*</b> .24.Δ	3000	Philips SLM G6	20W	830 Premium White	>80	High Efficiency	>0,9

High efficiency is the standard Keylight setting for all SLM G6 LED modules. For technical and warranty information regarding high efficiency, see last page of the catalogue. Standard system warranty is 5 years.